

ROTORTEX-EU

WWW.BENRON.COM



Light weight trigger gun includes a 4mm, 5mm, 6mm and 8mm spray tips.

P/N 16-311D Trigger Gun



Removable control switch mount on trigger gun.

P/N 19-163 Remote Switch



Short pole gun includes a 6mm, 7mm, 8mm, and 9mm spray tips, and a 15mm tip retainer. Recommended when spraying stucco.

P/N 10-127/19 Pole Gun



16m x 25.4mm material hose at 31bar burst pressure. Material hose includes: air hose, and control cable.

P/N 19-1560 Hose Kit



3 ball cleaning kit helps cleaning the material hose after use with water or air.

P/N 15-020 Ball Cleaning Kit



Air cleaning adapter to push cleaning ball through material hose when job is complete.

P/N 17-000 Air Cleaning Kit

* Optional selection

70 Liter material hopper includes a lid.



1L4 Rotor-Stator designed specially for aggregated materials.

1.55KW Stainless steel wash-guard electric motor.



Electric power single phase.....	230v 60hz & 240v 50hz
Maximum operating pressure.....	14 Bar
Maximum burst pressure.....	31 Bar
Maximum hose length.....	30 Meter ■
Maximum mixed aggregate.....	3 to 5mm
Maximum materail flow with 4.75:1 ratio.....	16 Lpm ■
Maximum material flow with 8.4:1 ratio.....	8 Lpm ■
Noise at 1 meter from unit.....	74 dB (at 4.7:1 ratio)
Noise at 1 meter from unit.....	81 dB (at 8.4:1 ratio)
Weight without accessories.....	77 Kg
Operating at maximum load.....	7 Amps
Ask for the special hose adapter P/N 19-1580 when spraying stucco.	
■ Depend on material viscosity	