



V-TEX 400

WWW.BENRON.COM

888-327-9839 or 818-787-4455

GFRC, GFRG, E.I.F.S, Fire-Proofing,
Stucco, and Most Cement Finish Products

Features Of The V-TEX 400

Powered by 5.5hp Honda engine.
5hp 220v Electric motor also available.

Smart hydraulic system with only
6 quarts of hydraulic oil.

Speed control for more surface
coverage.

Built-in 20cfm oil lubricant
air compressor.

Hydraulic hoses with a quick
disconnect fitting for reverse turning
when installing a new squeeze hose.

No internal moving parts come in
contact with the product being
pumped, this results in a reduce
of maintenance problems.

Maximum 100 ft. hose length
depends on material viscosity.

Maximum 4 square yards per
minute material flow.
Depends on material viscosity.

Maximum mixed aggregate up
to 1/4 inch.

1.25 in. x 50 ft. Material hose with
quick disconnect fitting, includes
an air hose, and control cable.

Short pole gun includes
4 spray tip and a special
blow-out cap retainer.

17 Gallon material hopper
includes a lid


Flat free front
caster wheel

P/N 19-400

1.25 inch material outlet

Air adapter used with cleaning
balls to clear material from
the hose.


3 ball cleaning kit helps
cleaning the material hose
after use with water or air.



P/N 19-460
Hose Kit



P/N 10-127/V
Pole Gun



P/N 17-000/V
Air Cleaning Adapter



P/N 15-020
Ball Cleaning Kit